

Town of Erin ROAD OCCUPANCY PERMIT

Permit
Number
PERMIT IS VALID WHEN NUMBER ASSIGNED

DO NOT COMPLETE SHADED AREAS

General Informat	IUII							
Company/Contractor Name:				Working For:				
Address:				File No:				
Business Phone:				Email:				
Applicants Name	(if differend fi	om above):		•				
After Hours Contact:				Contact Phone:				
Type of Work			Location					
☐ New			Road:			Boulevar	d: Yes 🔲 No 🗌	
Repair			At/Between:					
☐ Directional Bore Road Crossing			Borehole	☐ Fibre ☐ Road Access ☐ Pavement Cut				
DRAWINGS OF	THE PROP	OSED WOR	K ARE TO BE SUB	MITTED A	AS AN ATTACHME	NT		
		Approv	als will not be pro	vided with	out drawings			
Indicate North Arrov	w							
Special Provisions	<u> </u>	leted by Tow	n of Erin staff					
From General Con		<u> </u>	10-20 21	24	25-30 31-37	38-4	3	
Additional Condition	ions:							
	insurance as per To	own standards nad for. Failure to	·	ditional Insured	•	•	-	
Duration From:				Duration From:				
Requirement	rement To:			Approved To:				
Applicant Signature	olicant Signature Date		1	Town Approval		Date		
Application Fee: \$	110.00 Pa	d - Date:	TOE Signature	e:	Security Depos	it: Paid	Amount \$	
General Condition	<u>15</u>							
Prior to commencing work, stakeouts must be obtained from utilites in the Town of Erin.								
 The Area Foreman must be notified 48 hours before work is to commence When working, a copy of this permit and utility locates must be on site at all times. 								
_			cates must be on site at ceived by the Town of Er					
			permit, when required.					
•		·	•	e provided to	the Town of Erin for final	approval.		
7. Positive drainage	e whall be maint	ained during the	e course of work.					
8. No work is to be	done during rusl	n hour period (7	:00 am to 9:00 am, or 3:3	30 pm to 6:00	pm).			

Lane(s) of traffic must be maintained during working hours as per OTM Book 7, and traffic plan must be faxed to Area Foreman

prior to commencement of work. All lanes of traffic must be maintained when not working.

General Conditions - Continued

- 10. All utilities shall be protected and supported, to the satisfaction of the utility concerned.
- 11. All road surfaces and sidewalks shall be kept clear of obstructions and/or debris, to avoid hazard or inconvenience to the public.
- 12. Mud tracking or dust nuisance shall not be allowed. Any accumulation must be cleaned from the road and/or shoulders immediately. Cleaning instructions may be give by the Town field supervisory personnel. If at any point Town supervisory staff find that mud tracking or dust nuisance is excessive, the work shall be stopped.
- 13. The Applicant shall not cut, trim or interfere with any trees in the right-of-way without Town of Erin approval.
- 14. All changes and/or deviations from the submitted approved plans and/or locaitons whall be subject to re-approval from the Town of Erin.
- 15. Subject to Town of Erin approval, the use of steel plating shall not generally be permitted.
- 16. The road shall not be closed without the consent in writing of the Town of Erin Road Superintendent.
- 17. Property owners and/or residents shall receive a minimum of 24 hours written notice prior to temporary closing of an access to homes and businesses.
- 18. The applicant agrees and accepts full responsibility to supply, maintain, clean and place all barricades, warning signs, delineators and flashing lights, necessary for the protection of the public and the safe operation of the installation, at the applican't own expense, as per the Ontario Traffic Control Manual Book 7, Temporary Conditions latest revision. (Note: This manual depicts minimum standards, additional signing may be required by the Town of Erin.
- 19. All disturbed or affected areas to be maintained and guaranteed for two years after completion and acceptance of the work by the Town of Erin, at the applicant's expense.
- 20. The applicant accepts the Town of Erin's right to perform any necessary remedial work caused by the applican't operation, subject to the following conditions:
- a. The Town of Erin will give the applicant not less than twenty-four (24) hours notice of any remedial work required, except for emergency work.
- b. If at the expiration of the time allowed, the applicant or his/her contractor has not commenced remedial work to the Town's satisfaction, the Town of Erin may undertake to have this work done by whatever means it deems necessary.
- c. The applicant to reimburse the Town of Erin for all costs incurred uner 20a) antier 20b) and /or to supply the Town with a Security Deposit, for a specified amount, if requested.

Trenches and Pits

- 21. Trences shall be fully compacted by mechanical means, (roadway 100% SPMDD, roadside 95% SPMDD) and all surfaces restored to original condition. Positive drainage shall be maintained diring the course of the operation.
- 22. Mechanical and/or vibratory compaction equipment shall be on site prior to commencing work
- 23. Trench to be backfilled with Granular Subbase Course Class "B", in 150 mm (6") layers to 450 mm (18") below the road surface, and each lift shall be compacted using mechanical means.
- 24. Granular base Course Class "A" to 150mm (6") below the asphalt base in two layers and compacted to 100% SPMDD.

Boulevard Works

- 25. Shoulders to be repaired as per conditions number 30 and 31, cleaned of mud and clay, etc. and restored to original cross-section and appearance.
- 26. In grassed areas adjacent to homes and businesses, sodding is required as per OPSS 571. All other areas shall be seeded and straw mulched as per OPSS 572. Topsoil shall be placed to a minimum of 100mm depth prior to seeding or sodding as per Town of Erin requirements.
- 27. All disturbed ditches to be restored with at least four rows of sod placed in the bottom, as per OPSD 218.01.
- 28. Driveways shall be repaired in the same manner as the road as outlined below.
- 29. Asphalt strips and centre medians shall be restored to original condition or better.
- 30. Sidewalks shall be restored to match the Town of Erin's standards.

Road Works - Asphalt

- 31. On hot-mix asphalt pavement, cutting shall be done by means of sawing full depth to leave a clean straight edge. Excavation equipment such as backhoes, etc. shall not be used for this purpose. The adjoining pavement shall be protected from damage by equipment.
- 32. 75mm of Cold patching to be placed immediately as a temporary surface. Permanent pavement repairs using hot-mix asphalt shall be made within 14 days. All Town roads having heavy traffic times must be repaired immediately with hot-mix asphalt. Between November 15th and May 15th all cuts must be filled immediately with hot-mix (min 75mm). Under no curcumstances shall a cut be left with a granular surface.
- 33. Prior to permanent pavement repairs, a 300mm wide strip of asphalt each side of the excavation shall be removed by full depth saw cutting.
- 34. The application of a bonding agent (SS1 emulsion) shall be applied to all cold asphalt joins and exposed concrete faces as per OPSS 1103.
- 35. Limit of pavement construction joint to be sealed with "Tbond HMA Joint Tape", "Densoband" or approved equivalent.
- 36. 100mm HL8 (PG-58-28) placed in two 50mm lifts as per OPSS 310.
- 37. 50mm HL 3 (PGAC-58-28) placed as per OPSS 310.

Road Works - Concrete Base/Misc. Concrete

- 38. Existing concrete base must be saw cut a minimum of 300mm wider, each side of excavated trench.
- 39. Concrete Pavement Reinstatement OPSD 509.11.
- 40. 35 MPa high early strength concrete to be placed to match existing, as per OPSS 1350.
- 41. Concrete resoration shall not be open to traffic until concrete has reached 75 percent of the 28 day strength.
- 42. Unless otherwise noted, all concrete work shall comply with current CSA and OPSS standards and specifications.
- 43. Where the Town of Erin issues a permit on a Town road that thas been reconstructed and/or surfaced withing the past 5 years, the Town reserves the right to specify the extent of restoration required.